

Размеры в мм

Обозначение сверла	Применяемость	d	L	l_s	f	d_1	B	k	f	Угол наклона винтовой канавки α		
2300-1065		2,25	90	59		2,05	1,0			36°		
2300-1004		2,30				2,10						
2300-1066		2,35				2,15						
2300-1005		2,40				1,1					0,60	2,20
2300-1067		2,45										2,25
2300-1006		2,50	95	62					36°			
2300-1068		2,55									2,30	
2300-1007		2,60									2,35	
2300-1069		2,65									2,40	
2300-1008		2,70									1,2	0,65
2300-2701		2,75	2,50									
2300-1009		2,80	100	66						36°		
2300-1071		2,85									2,60	
2300-2702		2,90									2,65	
2300-1072		2,95									1,3	0,70
2300-1011		3,00							2,75			
2300-1073		3,10	106	69					36°			
2300-1012		(3,15)									2,80	
2300-1013		3,20									2,85	
2300-1014		3,30									2,90	
2300-1074		(3,35)									3,00	
2300-1015		3,40	1,5	0,80	3,10							
2300-1016		3,50			3,20							
2300-1017		3,60	1,6	0,85	3,30							
2300-1018		3,70			3,40							
2300-1019		3,80			3,50							
2300-2703		3,90	119	78					36°			
2300-1021		4,00								3,60		
2300-1075		4,10								3,70		
2300-1022		4,20								3,80		
2300-1076		(4,25)								3,90		
2300-1077		4,30	2,0	1,00	4,00							
2300-1078		4,40			4,10							
2300-1023		4,50	2,1	1,00	4,20							
2300-1079		4,60			4,30							
2300-2704		4,70	2,2	1,05	4,45							
2300-1024		4,80			4,50							
2300-1025		4,90	132	87					40°			
2300-1026		5,00								4,60		
2300-1081		5,10								4,70		
2300-1027		5,20								4,80		
2300-1028		5,30								4,90		
2300-1082		5,40	2,4	1,10	5,00							
2300-1029		5,50			5,10							
2300-1083		5,60	2,5	1,10	5,20							
2300-1084		5,70			5,30							
2300-2705		5,80	2,6	0,50	5,40							
2300-1085		5,90			5,50							
2300-1031		6,00	2,7		5,60							
2300-1086		6,10			148	97	5,60					